

The Right Choice ★★★★

Save up to \$800p.a. on your water heating bills!



Save money with the right choice of solar hot water system!

Key Eurosun benefits:

RATING

- Solar hot water system independently tested and verified with certified product license: SMK41036 AS/NZS 2712 that guarantees the highest product quality standards;
- Certification mark provided by Watermark: AS3498 WMK26521
- Longer tank life for Australian conditions due to the enamel coating made from titanium blue enamel powder;
- Solar collector is all aluminium outer casing, giving excellent corrosion resistance and proven long life;
- Modern sleek product design to match the sustainable home dream;
- Eurosun High Performance 300L is the most solar energy efficient system in the market because it has the highest energy rating (38 STCs);
- Eurosun highest energy rating (STCs) in the market maximises the government rebate to provide the best savings and minimises the booster usage;

Ring us on 1300 808 786 or visit eurosun.com.au




Customised configurations to meet your needs.

Eurosun rooftop high performance system (HP) comes with two configurations:

- 300L tank with 38 STCs: 2 collectors and suitable for a family size of 4 to 6.
- 200L tank with 28 STCs: 1 collector and suitable for a family size of 1 to 3.

Electric or gas booster options available for all configurations.



Tech Specifications*

Eurosun High Performance Solar 300L

TANK	SPECIFICATION
Storage Capacity	300 Litres
Boost Capacity(Electric)	150 Litres
Weight Empty	100 Kg
Weight Full	400 Kg
Working Pressure	0.85 Mpa
Collector Dimension (2)	2000X1000X76 mm
Solar Collector options	
Quantity	2 Panels
Gross Area	4 m2
Net Aperture	3.70 m2
Header Tube Diameter(mm)	ø22
Riser Tube Diameter(mm)	11 x ø8
Dry Weight	68 Kg
Fluid Capacity	2.60 Litres
Max. Working Pressure	1.60 Mpa
Absorber Coating	Blue Unite Sputtered Selective Surface
Absorber/Riser Material	Aluminium
Frame Material	Double Aluminium Alloy
Insulation Material	38 mm glass wool blanket
Glass	3.2 mm tempered low iron
Performance Rating	7.9 kWh/day
Electric Poost crossification	

Electric Boost specification

Power2.4 kWPerformance OptionsHigh performance

*Tech Specifications are subject to change due to continuous improvement policy.

Why Eurosun is different?

Our team combines technicians with over 60 years' of industry experience to offer residential & commercial energy solutions with the latest solar technology. We are proud of supplying quality solar systems with the best deals in the market.

- The Eurosun HP systems have longer tank lives due to the enamel coating that is made from titanium blue enamel powder that meets the Australian Watermark certification requirements and makes it durable for Australian conditions.
- The solar collector is all aluminium outer casing, giving excellent corrosion resistance and proven long life.
- The selective surface array is designed to maximise the solar energy contribution and looks good to.

Eurosun High Performance Solar 200L

TANK	SPECIFICATION
Storage Capacity	200 Litres
Boost Capacity(Electric)	100 Litres
Weight Empty	65 Kg
Weight Full	265 Kg
Working Pressure	0.85 Mpa
Collector Dimension (1)	2000x1220x76 mm
Solar Collector options	
Quantity	1 Panel
Gross Area	2.44 m2
Net Aperture	2.28 m2
Header Tube Diameter(mm)	ø22
Riser Tube Diameter(mm)	9 x ø8
Dry Weight	45 Kg
Fluid Capacity	1.60 Litres
Max. Working Pressure	0.80 Mpa
Absorber Coating	Blue Unite Sputtered Selective Surface
Absorber/Riser Material	Aluminium
Frame Material	Double Aluminium Alloy
Insulation Material	38 mm glass wool blanket
Glass	3.2 mm tempered low iron
Performance Rating	6.01 kWh/day
Electric Boost specification	
Power	2.4 kW
Performance Options	High performance

Our mission is to offer our customers the very best solar energy solutions tailored to their needs. This is why hundreds of West Australians have chosen to join the Eurosun Family, knowing they will receive the very best pre and post-sale experience.

Get the sense of the right solar hot water system choice.

Ring 1300 808 786 to discuss your needs. Or visit eurosun.com.au to fill out the 'Get in touch form' and one of our technicians will contact you within 24 hours.





1300 808 786 | eurosun.com.au